



TUF-TOP COATINGS

SINCE 1938

AQUA-TITE FP WATER/OIL REPELLENT

FOR CONCRETE, MASONRY, GRANITE*, STONE & MARBLE *

DESCRIPTION:

TUF-TOP AQUA TITE-FP WATER REPELLENT SEALER is a **water based** proprietary solution that provides a durable, transparent protective barrier against **oil and water** on concrete and other porous masonry or mineral surfaces. AQUA-TITE FP chemically bonds with the surface, providing long-term, invisible barrier protection.

USES:

CONCRETE & MASONRY

PAVERS & DECO BLOCK

NATURAL STONE

STUCCO

UN-POLISHED MARBLE/GRANITE

UN-GLAZED TILE

ADVANTAGES:

EXCELLENT WATER/OIL REPELLENT COATING FOR DRIVEWAYS, VEHICLE BAYS, LIGHT INDUSTRIAL FLOORING, AIRCRAFT HANGARS, CONCRETE, BRICK, GROUT, TERRA COTTA, SANDSTONE, UN-GLAZED DECORATIVE TILING, GYPSUM DRYWALL, UN-POLISHED STONE AND GRANITE SURFACES, STUCCO, ROOF TILES AND PLASTER.

PREPARATION:

For new concrete, masonry, mortar, bricks, etc. no special preparation is necessary other than making sure that the surface is clean, bare, not painted or sealed, and free from any waxes, mold release chemicals, or efflorescence, that may inhibit the penetration of AQUA-TITE FP. For older concrete, mortar, stone, etc., the surface must be free from dirt, oil, grease, efflorescence, and mold/mildew. Scrub with detergent or treat with bleach as needed and rinse thoroughly. Surface may be slightly damp when applying. Please note that AQUA-TITE FP may actually link to and pull some oils, grease, and other contaminants out of the concrete shortly after application. If this occurs, you may not get your desired waterproofing properties and will need to re-clean and apply an additional coat.

* A TEST PATCH IS RECOMMENDED TO CHECK FOR COMPATIBILITY.

APPLICATION:

Apply one thorough, soaking coat, allow to dry, apply a second "mist" coat.

Apply with roller, brush, pad or garden (hand pump) type sprayer. Do not use airless or conventional spray equipment.

Apply only when air and surface temperatures are between 40 - 100 degrees fahrenheit

On vertical surfaces, apply from the bottom up.

On horizontal surfaces, take care not to cause puddling by over-application.

LIMITATIONS:

DO NOT APPLY TO COATED, GLAZED, POLISHED OR SMOOTH SURFACES AS IT MAY ETCH OR DAMAGE THE SURFACE.

DO NOT APPLY TO GLASS, WOOD OR ALUMINIUM, ETCHING MAY OCCUR

DO NOT APPLY TO GLAZED ANYTHING

WILL NOT "BRIDGE" CRACKS WIDER THAN 1mm,

NOT FOR USE ON SHALE OR OTHER OIL ROCK

LIGHT COLORED SURFACES MAY SHOW THE SURFACE STAINING FROM CONTAMINANTS, BUT WILL BE REMOVABLE BY CLEANING

DO NOT APPLY TO PAINTED OR SEALED SURFACES

DO NOT APPLY WHEN IT MAY RAIN BEFORE AQUA-TITE FP WILL HAVE A CHANCE TO DRY.

DO NOT ALLOW TO FREEZE. STORE ABOVE 32 DEGREES FAHRENHEIT.

DO NOT APPLY WHEN AIR OR SURFACE TEMPERATURES ARE BELOW 40 DEGREES FAHRENHEIT OR ARE EXPECTED TO FALL THERE BEFORE COATING CAN DRY.

DRYING TIME:

Normally dries in 2-4 hours and cures in 24-48 hours. Low temperatures and high humidity can extend drying/curing time.

TECHNICAL DATA:

SOLIDS	100 % active , 6% weight
COVERAGE	150-400 sq.ft/gallon depending on porosity/texture of substrate
DILUENT	WATER-DO NOT DILUTE
CLEAN-UP	Soap and water
ODOR	None
APPEARANCE	Water clear/dries invisible
LIGHT STABILITY	Excellent
DURABILITY	Excellent
WATER RESISTANCE	Excellent
EPA AIM CATEGORY	Water repellent sealer

STAIN RESISTANCE - 2 HOUR SPOT TEST, CLEANED**

	LEADING BRAND	AQUA-TITE FP
WATER	0	0
OIL	5 ABSORBED	0
BACON GREASE	5 ABSORBED	0
COFFEE	1	0
SOY SAUCE	4	2
MUSTARD	2	0
BBQ SAUCE	5	1

- 0- BEST- NO STAINING
- 1- SLIGHT STAINING
- 2-LIGHT STAINING
- 3- MODERATE STAINING
- 4-HEAVY STAINING
- 5-ABSORBED/STAINED

** This product will inhibit most common staining elements, but should not be considered "stain proof". If certain staining elements are to be encountered commonly, a test should be made to determine the suitability of this product for the intended use. It is the sole responsibility of the owners or applicators to determine the suitability of this product for its intended use, and assumes all risks and liabilities in connection therewith.

CAUTION : DO NOT TAKE INTERNALLY. CLOSE CONTAINER AFTER USE. KEEP OUT OF REACH OF CHILDREN.

**MANUFACTURED BY: TUF-TOP COATINGS DIVISION OF MARINE INDUSTRIAL PAINT CO.,INC. ST. PETERSBURG, FL.
PHONE 727-527-3882 800-459-3882 FAX 727-521-1405 WWW.TUF-TOP.COM**

LIMITATION OF LIABILITY: The Manufacturer and/or seller warrants that if any goods supplied prove defective in workmanship or material, that Manufacturer and/or seller shall replace them or refund the purchase price. This warranty is made in lieu of any and all other warranties expressed or implied. Before application, the User shall determine the suitability of the product for his intended and User assumes all risks and liabilities. whatsoever in connection therewith Under no circumstances shall the Manufacturer and/or Seller be liable for incidental, consequential or other damages for alleged negligence, breach or warranty, or strict liability arising out of use or handling of this product. The sole liability of Manufacturer and/or Seller for any claims arising out of the use or sale of the product shall be for User's purchase price.